

C4-3-393-R002

C4-FN gas refilling device for high-voltage

Portable in a transport case wire-braided hose, DILO-couplings DN8 and DN20, pressure range 0 up to 16 bar

For safe refilling of gaseous stored C4-FN gas mixtures by overpressure

The handy device allows filling of electrical equipment with C4-FN gas mixtures directly from the cylinder by overpressure. The primary gauge of the pressure reducer displays the cylinder pressure in bar, psi and kPa. The secondary gauge indicates the desired filling pressure to be set easily by means of the handle. The cylinder pressure can be reduced to the desired filling pressure by the integrated pressure reducer.

The use of gastight and selfclosing DILO couplings guarantees emission-free gas handling during the refilling process.



The actual product may differ slightly from the image.

Standard version

- pressure reducer for C4-FN gas mixtures
- SF6 cylinder connection W 21.8 x 1/14"
- primary gauge NG63, class 1.6, 0 - 60 bar
- secondary gauge NG100, class 1.0, 0 - 16 bar
- indication units in bar, kPa,psi
- wire-braided hose 5 m long hose DN8
- DILO couplings DN8 and DN20

Special features

- Gas type: C4-FN
- Filling of gas: 0 - 16 bar
- DILLO couplings: DN8/DN20
- Operation: manual
- Transport case: yes

Advantages & functions

- most common global cylinder connections available as accessories
- stowed in a transport case

Technical data

Weight	7.5 kg
Dimensions (W x H x D)	420 x 180 x 500 mm with transport case

Note

Other versions are available on request.