

CA-3-001-R001

CA gas refilling device, mobile as cylinder cart with rubber hose

For safe refilling of gas into gas compartments by overpressure

Refilling device as cylinder cart for comfortable on-board carrying of a gas cylinder. The primary gauge of the pressure reducer displays the cylinder pressure in bar, psi and kPa. The secondary gauge indicates the desired filling pressure to be set easily by means of the handle. The cylinder pressure can be reduced to the desired filling pressure by the integrated pressure reducer. The use of gastight and selfclosing DILO CA-couplings guarantees emission-free gas handling during refilling.



The actual product may differ slightly from the image.

Standard version

- pressure reducer for CA
- CA cylinder connection G 3/4 & G 5/8
- primary gauge NG63, class 1.6, 0 - 315 bar
- secondary gauge NG100, class 1.0, 0 - 16 bar
- indication units in bar, ps, kPa
- ball valve DN8 with hand wheel
- 6 m long rubber hose DN8
- DILO CA-couplings DN8 and DN20 M24x1,5 - M50x2
- solid tyre wheels Ø 250 mm
- paint: green-anthracite

Special features

- Gas type: CA
- Filling of gas: 0 - 16 bar
- DILO couplings: DN8/DN20
- Operation: manual

Advantages & functions

- stable frame
- hose reel
- couplings can be exchanged without any gas loss

Technical data

Dimensions (W x H x D)	540 x 1.360 x 480 mm
Weight	30 kg
Ambient temperature	0 to +45 °C
Operating temperature	0 to +45 °C
Storage temperature	-20 to +60 °C

Packaging

3-262-R001-C	Packing for 3-001-R001 / 3-001-R002
--------------	-------------------------------------