



CA-3-393-R001

CA gas refilling device

With rubber hose, DILO CA-couplings DN8 and DN20, pressure range 0 up to 16 bar

For safe refilling of CA gas into gas mixtures compartments by overpressure

The handy device allows filling of electrical equipment with CA gas directly from the cylinder by overpressure. The primary gauge of the pressure reducer displays the cylinder pressure in bar, psi and kPa. The secondary gauge indicates the desired filling pressure to be set easily by means of the handle. The cylinder pressure can be reduced to the desired filling pressure by the integrated pressure reducer.

The use of gastight and selfclosing DILO CA-couplings guarantees emission-free gas handling during the refilling process.



The actual product may differ slightly from the image.

Standard version

- pressure reducer for CA
- CA cylinder connection G 3/4 & G 5/8
- primary gauge NG63, class 1.6, 0 - 300 bar
- secondary gauge NG100, class 1.0, 0 - 16 bar
- indication units in bar, kPa,psi
- 5 m long rubber hose DN8
- DILO CA-couplings DN8 and DN20 M24x1,5 - M50x2

Special features

- Gas type: CA
- Filling of gas: 0 - 16 bar
- DILO couplings: DN8/DN20
- Operation: manual

Advantages & functions

Technical data

Weight	7.5 kg
--------	--------

Note

Other versions are available on request.