

CA-3-393-R002

### CA gas refilling device

Portable in a transport case with rubber hose, DILO CA couplings DN8 and DN20, pressure range 0 up to 16 bar

#### For safe refilling of CA gas into gas mixtures compartments by overpressure

The handy device allows filling of electrical equipment with CA gas directly from the cylinder by overpressure. The primary gauge of the pressure reducer displays the cylinder pressure in bar, psi and kPa. The secondary gauge indicates the desired filling pressure to be set easily by means of the handle. The cylinder pressure can be reduced to the desired filling pressure by the integrated pressure reducer.

The use of gastight and selfclosing DILO CA-couplings guarantees emission-free gas handling during the refilling process.



*The actual product may differ slightly from the image.*

#### Standard version

---

- pressure reducer for CA
- CA cylinder connection G 3/4 & G 5/8
- primary gauge NG63, class 1.6, 0 - 315 bar
- secondary gauge NG100, class 1.0, 0 - 16 bar
- indication units in bar, kPa,psi
- 5 m long rubber hose DN8
- DILO CA-couplings DN8 and DN20 M24x1,5 - M50x2

#### Special features

---

- Gas type: CA
- Filling of gas: 0 - 16 bar
- DILO couplings: DN8/DN20
- Operation: manual
- Transport case: yes

## Advantages & functions

---

- stowed in a transport case

## Technical data

---

|                        |  |
|------------------------|--|
| Weight                 | 7.5 kg                                 |
| Dimensions (W x H x D) | 420 x 180 x 500 mm with transport case |

## Note

---

Other versions are available on request.